

Since 1985



Product Information Insurbond-106 Contact Adhesive



<p>Insurbond-106 Contact Adhesive</p>	<p>Is a Water Base one-component adhesive with very strong adhesive properties on all normally occurring substrates and to be used for bonding Insuwrap PVC Waterproofing membranes to concrete, cement plaster & metal sheets; where required.</p>	
<p>Technical Data</p>	<p>Colour Open time: Coverage: Application: Ventilating Time</p>	<p>Cream 1 hour approximately 300 to 400 g/m² Depending on surface. Brush or roller Depending on temperature conditions, relative humidity and quantity applied (ventilation test). Low temperatures slow down and high temperature speed up ventilation. Within days depending on climatic conditions. Up to 12 months in a covered place with good ventilation.</p>
<p>Application</p>	<p>Concrete, aerated concrete, bricks and roughcast render Plywood, Fiber cement boards. Polyurethane rigid foam boards with appropriate glass facing. Perlite boards. Galvanized metal sheet, Stainless steel and aluminum. Other applications on request.</p>	
<p>Advantages</p>	<ul style="list-style-type: none"> ● Provides high adhesion properties to non woven geotextile with different substrates ● Environmentally safe. ● Easy Application. ● Quick Setting. ● Suitable to most of surfaces. ● Good Coverage. ● Heat Resistant. ● Water Resistance. 	



Since 1985



Product Information Insurbond-106 Contact Adhesive

Directions For Use	The surface has to be leveled, sound, dry and clean. Apply the adhesive uniformly on the substrate using a fine trowel, brush or roller. Allow the adhesive to set for approx. 15-20 minutes to become tacky then place the following material. Clean any excess with water immediately.
Storage & Shelf Life	Store under cover, protect from direct sunlight and high temperature (>30°C). Shelf life is up to 12 months in unopened container when stored as directed. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. Please follow law of the land.
Cleaning	Clean all the tools with warm water immediate
Health & Safety	<p>As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.</p> <p>Inhalation: Inhalation of vapor or mist should be avoided. Symptoms include coughing, wheezing, laryngitis and shortness of breath, headache, nausea and vomiting. Immediately shift victim to fresh air and if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help.</p> <p>Eye Contact: Flush eyes with water for 15 minutes and call for medical help.</p> <p>Ingestion Causes nausea, vomiting and loss of consciousness. If accidentally swallowed do not induce vomiting rather call for medical help immediately.</p> <p>Skin contact Flush with water or soap and water until all traces have been removed. Seek medical attention if required</p>

A Member of **rar** & Sons Group
Waterproofing and Wrapping
Products Co. Ltd.

011-26111111
011-26111111

011-26111111
011-26111111
011-26111111
011-26111111